

1. 製造商名稱
 2. 產品名稱

3. 產品規格
 4. 產品圖樣
 5. 產品照片

6. 產品說明書
 7. 產品檢驗報告
 8. 產品檢驗合格證明

9. 產品檢驗合格證明
 10. 產品檢驗合格證明
 11. 產品檢驗合格證明
 12. 產品檢驗合格證明


13. 產品檢驗合格證明

14. 產品檢驗合格證明

15. 產品檢驗合格證明

16. 產品檢驗合格證明

17. 產品檢驗合格證明





Product Service

Attestation of Conformity

No. N8A 15 09 93168 002

Model(s):

MG12A-08, MG16A-07, MG16A-10, MG20A-11, MG20A-14,
MG25A-16, MG25A-18, MG32A-22, MG32A-25, MG40A-25,
MG40A-30, MG50A-32, MG50A-40, MG63A-46, MG63A-50,
PG7A-08, PG9A-05, PG9A-08, PG11A-07, PG11A-10,
PG13.5A-08, PG13.5A-12, PG16A-11, PG16A-14, PG21A-16,
PG21A-18, PG29A-22, PG29A-25, PG36A-25, PG36A-30,
PG42A-32, PG42A-40, MGB12S-06B, MGB12-07B, MGB12L-07B,
MGB16S-08B, MGB16SL-08B, MGB16-10B, MGB16L-10B, MGB18-10B,
MGB18L-10B, MGB20S-12B, MGB20-14B, MGB20L-14B, MGB25S-14B,
MGB25-18B, MGB25L-18B, MGB32-22B, MGB32-25B, MGB40-32B,
MGB50-40B, MGB63-46B, PGB7-07, PGB9-08, PGB13.5-12,
PGB16 -14, PGB19 -14, PGB21-18, PGB25-20, PGB29-25,
PGB36-32, PGB42-41, PGB48-46

Parameters:

Material of the cable glands:	Non-metallic
Type of cable anchorage:	Anchorage Type A
Impact category:	Category 1
Degree of protection:	IP54
Temperature range:	-40°C to 85 °C
Sealing system:	With a single orifice seal

Tested according to:

EN 62444:2013